

Qmed®

Variable area **oxygen flowmeters**

Qmed® flowmeters are instant flow measuring devices suitable for the dosage of medical gases. They are manufactured in version with compensated or not compensated pressure and in single or twin configuration in order to allow a double and independent gas supply using a single gas source.

STRUCTURE

The flowmeters type **Qmed®** fit a needle valve with a knob in color code for the immediate identification of the supplied gas. The body is made of aluminium making it extremely light and giving the possibility to obtain different finishing solutions such as chrome-plating or anodising, this last case in different customised colours.

The measure group is made of high resistance polycarbonate, a high mechanical resistance material that, together with the chrome-plated brass nipples and the aluminium body, makes this device ideal for the toughest applications. Moreover the outlet nipple can be easily manually removed and replaced by the operator, to meet any immediate application requirements.

SOLUTIONS AND OPTIONS

The flowmeters type **Qmed®** are available in different solutions of pressure calibration and medical gases, various options of scale, normal or extended (L version) to allow a better reading of the indicated values and in several configurations of inlet and outlet connections offering a wide range of combinations to fit every application need.

Main information



Qmed® can be manufactured in single or twin configuration in order to allow double and separate gas supply using a single gas source.



The outlet nipple can be easily manually removed and replaced by the operator, to meet any immediate application requirements.

Related products



Humidifiers
from p. 47



Oxygen Probes and Accessories
from p. 55

SIZES (LxWxH) 82x33x142 mm

WEIGHT 0.15 Kg

SUPPLY MAX. PRESSURE 600 kPa

STANDARD END OF SCALE VALUES - 400 kPa 1 L/min. · 4 L/min. · 5 L/min. · 10 L/min. · 15 L/min. · 20 L/min. · 30 L/min. · 50 L/min.

ACCURACY ±10% read value or ±0.5 L/min. if greater (±10% E.O.S. value for flow E.O.S. ≤ than 1 L/min.)

STANDARD INLET CONNECTION ISO G 1/8" F. · ISO G 1/4" M. · 1/4" NPT M. · 3/8" ISO 3253 F. · M 12x1 F.

STANDARD OUTLET CONNECTION 1/4" ISO 3253 M. · 3/8" ISO 3253 M. · M 12x1.25 M. · 9/16" UNF EN 13544-2 M.

- 1 **Outlet connection** easy to remove and to replace.
- 2 **Anodized body version** available in different colours.



Qmed® twin
chrome-plated aluminium body
twin construction

Qmed®
chrome-plated aluminium body
single construction



1



2