

EASYSAFE®

Safety jar

The **EASYSAFE®** safety jar is a medical device designed and manufactured for applications of "high flow and high vacuum".

STRUCTURE

Designed for use with the **EASYVAC®** vacuum regulators, **EASYSAFE®** is used to protect the equipment and plant upstream, should the overflow valve in the main container not be working properly. Made of a strong and reliable techno-polymer (polysulphone), the **EASYSAFE®** safety jar is autoclavable (134 °C - 18 min.), has an overflow floating valve and a housing designed to fit an antibacterial filter to guarantee the complete suction system protection against contamination.

CAPACITY

This safety jar has a deliberately reduced capacity (approx. 50 ml) so that even a small presence of fluid can immediately activate the floating valve to stop the suction.

Main information



The vacuum hose connector and the quick release connection nut make the **EASYSAFE®** simple and easy to set up and to remove from the **EASYVAC®** vacuum regulator.



The **EASYSAFE®** safety jar is made of polysulfone and fully autoclavable (134 °C - 18 min.).

Related products



Vacuum regulators
from p. 69



Venturi suction units
from p. 79



Collection jars
p. 96

SIZES (LxWxH) 70x90x75 mm

WEIGHT 0.08 Kg

OVERFLOW SYSTEM floating valve

PATIENT CONNECTION hose connector Ø 8.0÷9.2 mm

MAXIMUM APPLICABLE VACUUM VALUE -950 mbar / 5 min.

CAPACITY APPROXIMATELY 50 ml

- 1 **Quick release** lock-unlock nut system.
- 2 **Housing for antibacterial filter**
Ø 50 mm (optional).
- 3 **EASYVAC®** -1000 mbar fitted
with **EASYSAFE®** (optional).

EASYVAC® vacuum regulator, p. 74

