


DF

FLOW SELECTOR FOR AEROSOL THERAPY

The **DF** flow selector, used in conjunction with **Rs** and **Qmed**[®] flowmeters, allows to divert the supplied gas through an humidifier or through a hose connector to connect devices used for aerosol therapy.

It fits a threaded ring to connect the flowmeter, while the flow can be easily directed to the humidifier for oxygen therapy, through the axial outlet, otherwise the flow can be diverted through a side hose connector for aerosol therapies.


A synoptic printed on the body of the **DF** flow selector helps the operators to easily control the selected flow direction.



01



02



03

01 CONNECTION TO THE FLOWMETERS WITH DIFFERENT THREADS

02 CONNECTION TO THE HUMIDIFIERS WITH DIFFERENT THREADS

03 DF FLOW SELECTOR INTEGRATED IN THE **Rs** FLOWMETER

➤ **OXITER**[®] OXYGEN THERAPY SINGLE-PATIENT HUMIDIFIER, PAGE 38

➤ **Rs** VARIABLE AREA OXYGEN FLOWMETER, PAGE 18



TECHNICAL SPECIFICATIONS | DF

SIZES (LxWxH)	32x54x69 mm
WEIGHT	0.16 Kg
SUPPLY MAX. PRESSURE	500 kPa
MAX. PRESSURE DROP WITH FLOW 15 L/MIN. O₂	9.20 kPa
INLET CONNECTION	1/4" ISO 3253 F. M12x1.25 F. • 9/16" UNF EN 13544-2 F.
OUTLET CONNECTION	1/4" ISO 3253 M. M12x1.25 M. • 9/16" UNF EN 13544-2 M.
HOSE CONNECTOR FOR AEROSOL CIRCUIT	Ø 6÷9 mm
PRESSURE DROP AT THE HUMIDIFIER SIDE WITH FLOW 20 L/min.	17 kPa
PRESSURE DROP AT THE AEROSOL SIDE WITH FLOW 20 L/min.	34 kPa