

EASYSAFE®

SAFETY JAR

The **EASYSAFE®** safety jar is a medical device designed and manufactured for applications of “high flow and high vacuum”.

Designed for use with the **EASYVAC®** vacuum regulators, **EASYSAFE®** is used to protect the equipment and plant upstream, should the overflow valve in the main container not be working properly. Made of a strong and reliable techno-polymer (polysulphone), the **EASYSAFE®** safety jar is autoclavable (134 °C - 18 min.), has an overflow floating valve and a housing designed to fit an antibacterial filter to guarantee the complete suction system protection against contamination.

This safety jar has a deliberately reduced capacity (approx. 50 ml) so that even a small presence of fluid can immediately activate the floating valve to stop the suction. The vacuum hose connector and the quick release connection nut make the **EASYSAFE®** simple and easy to set up and to remove from the **EASYVAC®** vacuum regulator.



01 QUICK RELEASE LOCK-UNLOCK NUT SYSTEM

02 HOUSING FOR ANTIBACTERIAL FILTER Ø 50 MM (OPTIONAL)

EXAMPLE OF COMPACTNESS
AND SIMPLICITY: **EASYSAFE®** SAFETY JAR
WITH ANTIBACTERIAL FILTER
FITTED WITH **EASYVAC®** -1000 mbar
VACUUM REGULATOR.



➤ **EASYVAC®** VACUUM REGULATOR, PAGE 58



TECHNICAL SPECIFICATIONS | EASYSAFE®

SIZES (LxWxH)	70x90x75 mm
WEIGHT	0.08 Kg
OVERFLOW SYSTEM	floating valve
PATIENT CONNECTION	hose connector Ø 8.0÷9.2 mm
MAXIMUM APPLICABLE VACUUM VALUE	-950 mbar / 5 min.