

# VA - VD

## Water manometers

The water manometers VA and VD series are used for accurate adjustment of vacuum values in the suction in interventions of gastric and chest drainage.

### STRUCTURE

The devices are made essentially of an anodized aluminium head manufactured in anodized aluminum in which a needle valve acts for suction rate adjustments, and where a primary polycarbonate tube containing the water gets the function of measurement and calibration. Inside the tube, a graduated dipstick having scale up to 40 cm (VA/600 and VD/600) or up to 70 cm (VA/1000 and VD/1000) is used to adjust the hydraulic head necessary for the treatment.

### Main information



The VD series has also a secondary tube for fine adjustment of hydraulic head values, and, consequently, of the suction value, up to a maximum value of 5 cm.

### Related products



Vacuum regulators  
from p. 70



Venturi suction units  
from p. 79



Collection jars  
p. 96

	VA/600	VA/1000	VD/600	VD/1000
<b>SIZES (LxWxH)</b>	74x97x730 mm	74x97x1130 mm	78x127x730 mm	78x127x1130 mm
<b>WEIGHT</b>	0.58 Kg	0.75 Kg	0.91 Kg	1.10 Kg
<b>ADJUSTMENT RANGE</b>	0 ÷ -40 cm H <sub>2</sub> O	0 ÷ -70 cm H <sub>2</sub> O	0 ÷ -40 cm H <sub>2</sub> O	0 ÷ -70 cm H <sub>2</sub> O
<b>INLET MAX. DEPRESSION</b>	-950 mbar			
<b>INLET CONNECTION</b>	ISO G. 1/4" M.		hose connector Ø 7.5 mm	
<b>OUTLET CONNECTION</b>	hose connector Ø 7.5 mm			

- 1 Anodized aluminum upper body, with vacuum adjusting knob.
- 2 Graduated scale, detail.



1



2