Electric contacts type A

The electric contacts type “A” assure, when coupled to the flowmeters type KD-KD/Z, SW, LB, intervention points adjustable on the whole instrument scale. The feeders are assembled in a wheaterproof case with IP65 electric protection.

COMPANY INFO: Flow Meter Spa - Via del Lino, 6 - 24040 Levate - Bergamo - ITALY
Tel. +39 035 594047 I Fax +39 035 594821 I info@flowmeter.it I **www.flowmeter.it**
P.IVA/VAT IT01737040160

TYPE	SENSORS	ELECTRIC CONTACTS	CONTACTS ELECTRIC VALUES	AVAILABLE FOR
A 30 S	n° 1 Inductive proximity transducer	n° 1 SPDT	250V 5A 50HZ	"KD-KD/Z, SW"
A 30 D	n° 2 Inductive proximity transducers	n° 2 SPDT	250V 5A 50HZ	"KD-KD/Z, SW"
A 30 S BIS	n° 1 Inductive proximity transducer	n° 1 SPDT with double stable contact	250V 5A 50HZ	"KD-KD/Z, SW"
A 30 SN	n° 1 Inductive proximity transducer NAMUR	n° 1 SPDT	250V 5A 50HZ	"KD-KD/Z, SW"
A 30 SN BIS	n° 1 Inductive proximity transducer NAMUR	n° 1 SPDT with double stable contact	250V 5A 50HZ	"KD-KD/Z, SW"
A 30 AF	n° 1 Photocell with infra-red barrier	n° 1 SPDT with programmable time	250V 5A 50HZ	"KD-KD/Z, SW, LB"

Power: 110V/220V ± 5% 50 Hz
Electric case: 127x87x56 mm
Cable connectors: PG7"

COMPANY INFO: Flow Meter Spa - Via del Lino, 6 - 24040 Levate - Bergamo - ITALY
Tel. +39 035 594047 | Fax +39 035 594821 | info@flowmeter.it | **www.flowmeter.it**
P.IVA/VAT IT01737040160